



**SPECIFICATIONS: LINEAR POWER SUPPLY IHAS-1.2/OVP**

**MADE IN THE U.S.A.**

<p><b>VAC INPUT:</b></p> <ul style="list-style-type: none"> <li>100/230 VAC, +/-10%</li> <li>FREQUENCY RANGE: 47-440 HZ</li> </ul>	<p><b>VAC JUMPERING AND FUSING REQUIREMENTS:</b> SILKSCREENED ON CHASSIS FOR TRANSFORMER PRIMARY TERMINALS</p> <table border="1"> <tr> <td>For Use at</td> <td>115VAC</td> <td>230VAC</td> </tr> <tr> <td>Jumper</td> <td>1&amp;3, 2&amp;4</td> <td>2&amp;3</td> </tr> <tr> <td>Apply AC</td> <td>1&amp;4</td> <td>1&amp;4</td> </tr> <tr> <td>FUSE INPUT AT</td> <td>0.25A</td> <td>0.125A</td> </tr> </table>	For Use at	115VAC	230VAC	Jumper	1&3, 2&4	2&3	Apply AC	1&4	1&4	FUSE INPUT AT	0.25A	0.125A
For Use at	115VAC	230VAC											
Jumper	1&3, 2&4	2&3											
Apply AC	1&4	1&4											
FUSE INPUT AT	0.25A	0.125A											
<p><b>VDC OUTPUT:</b></p> <ul style="list-style-type: none"> <li>5 VDC @ 1.2 AMP</li> </ul>	<p><b>OVERVOLTAGE PROTECTION:</b></p> <ul style="list-style-type: none"> <li>PROVIDED. FACTORY SET AT 6.2VDC, +/-0.4VDC</li> </ul> <p><b>SHORT CIRCUIT PROTECTION:</b></p> <ul style="list-style-type: none"> <li>AUTOMATIC FOLDBACK</li> </ul> <p><b>OVERLOAD PROTECTION:</b></p> <ul style="list-style-type: none"> <li>AUTOMATIC CURRENT LIMIT</li> </ul>												
<p><b>LINE REGULATION:</b></p> <ul style="list-style-type: none"> <li>+/- 0.05% FOR A 10% LINE CHANGE</li> </ul>	<p><b>LOAD REGULATION:</b></p> <ul style="list-style-type: none"> <li>+/- 0.05% FOR A 50% LOAD CHANGE (DERATE OUTPUT CURRENT 10% FOR 50 HZ OPERATION)</li> </ul>												
<p><b>OUTPUT RIPPLE:</b> 5.0mV PK-PK MAXIMUM</p>	<p><b>TRANSIENT RESPONSE:</b> &lt; 50 µsec per 50% LOAD CHANGE</p>												
<p><b>TEMPERATURE RATINGS:</b></p> <ul style="list-style-type: none"> <li>OPERATING: 0°C TO 50°C FULL RATED DERATED LINEARLY TO 40% @ 70°C</li> <li>STORAGE: -40°C TO +85°C</li> </ul>	<p><b>TEMPERATURE COEFFICIENT:</b></p> <ul style="list-style-type: none"> <li>TYPICAL: 0.01%/DEGREE C</li> <li>MAXIMUM: 0.03%/DEGREE C</li> </ul>												
<p><b>STABILITY:</b> +/- 0.3% FOR 24 HOURS AFTER 1 HOUR WARM-UP</p>	<p><b>EFFICIENCY (TYPICAL): 45%</b></p>												
<p><b>VIBRATION:</b></p> <ul style="list-style-type: none"> <li>MIL-STD-810G, METHOD 514.6, CATEGORY 1, PROCEDURE1</li> <li>RANDOM VIBRATION 10Hz - 2KHz, 6.15 grams (3 axis)</li> </ul>	<p><b>SHOCK:</b></p> <ul style="list-style-type: none"> <li>MIL-STD-810G, METHOD 516.6, PROCEDURE III</li> <li>OPERATING: 20 GPK</li> </ul>												
<p><b>REMOTE SENSING:</b> NOT PROVIDED</p>	<p><b>EMI/RFI:</b> INHERENT LOW CONDUCTED AND REDIATED NOISE LEVELS.</p> <ul style="list-style-type: none"> <li>EMI: FCC CFR TITLE 47 PART 15 SUB-PART B</li> <li>RFI: EN55022/CISPR22-LEVEL B COMPATIBILITY</li> </ul>												

UL recognized for US and Canada – File#E133338/ CE Mark: LVD 92/59/EEC/ RoHs-5 Lead in Solder Exemption  
 US and Canadian (Bi-National) standards: ANSI/UL 60950-1/-21; CAN/CSA C22.2 #60950-1/-21; IEC 60950-1

## CASE SIZE: A

